



TRITON-PDH.COM
6757 W. Charleston Boulevard, Suite B
Las Vegas, NV 89146
Admin@triton-pdh.com

Examination for ADA - Accessibility Standards

1. ARCHITECTURAL BARRIERS ACT OF 1968 as amended sets standards for facility accessibility by physically handicapped persons for Federal and federally-funded facilities. These standards are to be applied during the design, construction, and alteration of buildings and facilities to the extent required by the Architectural Barriers Act of 1968, as amended.
 - a. true
 - b. false
 - c. not enough information available
 - d. Too many variables for specific answer

2. An accessible site shall meet the following minimum requirement:
 - a. At least one accessible route complying with 4.3 shall be provided within the boundary of the site from public transportation stops, accessible parking spaces, passenger loading zones if provided, and public streets or sidewalks to an accessible building entrance.
 - b. At least one accessible route complying with 4.3 shall connect accessible buildings, facilities, elements, and spaces that are on the same site.
 - c. All objects that protrude from surfaces or posts into circulation paths shall comply with 4.4.
 - d. All the above

3. The minimum clear width for single wheelchair in a continuous passage shall be _____.
 - a. 30 inches
 - b. 32 inches
 - c. 36 inches
 - d. 38 inches

4. The space required for a wheelchair to make a 180-degree turn is a clear space of _____.
 - a. 36 inches
 - b. 48 inches
 - c. 60 inches
 - d. 72 inches

5. If the clear floor space only allows forward approach to an object, the maximum high forward reach allowed shall be _____.
 - a. 15 inches
 - b. 24 inches
 - c. 36 inches
 - d. 48 inches

6. The minimum low forward reach is _____.
 - a. 15 inches
 - b. 24 inches
 - c. 30 inches
 - d. 36 inches

7. If an accessible route has less than 60 inches clear width, then passing spaces at least 60 inches by 60 inches shall be located at reasonable intervals not to exceed _____.
 - a. 50 feet
 - b. 100 feet
 - c. 150 feet
 - d. 200 feet

8. An accessible route with a running slope greater than 1:20 is a ramp and shall comply with 4.8. Nowhere shall the cross slope of an accessible route exceed _____.
 - a. 1:25
 - b. 1:50
 - c. 1:100
 - d. flat, no cross slope

9. If gratings are located in walking surfaces, then they shall have spaces no greater than _____ wide in one direction.
 - a. 3/8 inch
 - b. 1/2 inch
 - c. 5/8 inch
 - d. 3/4 inch

10. If gratings have elongated openings, then they shall be placed so that the long dimension is _____ to the dominant direction of travel.
- perpendicular
 - parallel
 - at a 45° angle
 - at a 30° angle
11. Parking spaces for disabled people shall be at least _____.
- 96 inches
 - 102 inches
 - 108 inches
 - 114 inches
12. Passenger loading zones shall provide an access aisle at least _____ wide and 20 ft long adjacent and parallel to the vehicle pull-up space.
- 48 inches
 - 60 inches
 - 72 inches
 - 84 inches
13. The minimum width of a curb ramp shall be _____ , exclusive of flared sides.
- 36 inches
 - 42 inches
 - 48 inches
 - 54 inches
14. If a curb ramp is located where pedestrians must walk across the ramp, or where it is not protected by handrails or guardrails, then it shall have flared sides; the maximum slope of the flare shall be _____.
- 1:5
 - 1:10
 - 1:15
 - 1:20
15. Ramps shall have level landings at the top of each run and when ramps change direction, but are not required at the bottom.
- true
 - false
 - not enough information for a specific answer
 - too many variables for a specific answer
16. The landing length of a ramp shall be a minimum of _____ clear.
- 48 inches
 - 54 inches
 - 60 inches
 - 66 inches

17. The clear space between the handrail and the wall shall be _____.
- 1-1/4 inches
 - 1-1/2 inches
 - 1-3/4 inches
 - 2 inches
18. Top of handrail gripping surfaces shall be mounted between _____ above ramp surfaces.
- 30 and 34 inches
 - 32 and 36 inches
 - 34 and 38 inches
 - 36 and 40 inches
19. On any given flight of stairs, all steps shall have uniform riser heights and uniform tread widths. Stair treads shall be no less than _____ wide, measured from riser to riser.
- 10 inches
 - 11 inches
 - 12 inches
 - 13 inches
20. Stair nosings shall project no more than _____.
- 1-1/4 inches
 - 1-1/2 inches
 - 1-3/4 inches
 - 2 inches
21. Handrails shall be continuous along both sides of stairs. The inside handrail on switchback or dogleg stairs shall always be continuous.
- true
 - false
 - not enough information for a specific answer
 - too many variables for a specific answer
22. Call buttons in elevator lobbies and halls shall be centered at _____ above the floor.
- 36 inches
 - 38 inches
 - 40 inches
 - 42 inches

23. The minimum time for elevator doors to remain fully open in response to a car call shall be ____ seconds.
- a. 3 seconds
 - b. 5 seconds
 - c. 6 seconds
 - d. 9 seconds
24. Doorways shall have a minimum clear opening of ____ with the door open 90 degrees, measured between the face of the door and the stop.
- a. 30 inches
 - b. 32 inches
 - c. 34 inches
 - d. 36 inches
25. The minimum space between two hinged or pivoted doors in series shall be ____ plus the width of any door swinging into the space.
- a. 36 inches
 - b. 42 inches
 - c. 48 inches
 - d. 54 inches
26. Thresholds at doorways shall not exceed ____ in height for exterior sliding doors.
- a. 1/2 inch
 - b. 5/8 inch
 - c. 3/4 inch
 - d. 7/8 inch
27. The height of water closets shall be _____, measured to the top of the toilet seat.
- a. 16 to 18 inches
 - b. 17 to 19 inches
 - c. 18 to 20 inches
 - d. 19 to 21 inches
28. Controls for flush valves shall be mounted on the wide side of toilet areas no more than ____ above the floor.
- a. 40 inches
 - b. 42 inches
 - c. 44 inches
 - d. 46 inches

29. Toilet stall doors shall comply with 4.13. If toilet stall approach is from the latch side of the stall door, clearance between the door side of the stall and any obstruction may be reduced to a minimum of ____.
- 40 inches
 - 42 inches
 - 44 inches
 - 46 inches
30. Urinals shall be stall-type or wall-hung with an elongated rim at a maximum of ____ above the floor.
- 16 inches
 - 17 inches
 - 18 inches
 - 19 inches
31. A clear floor space ____ by 48 inches shall be provided in front of urinals to allow forward approach.
- 30 inches
 - 32 inches
 - 34 inches
 - 36 inches
32. Lavatories shall be mounted with the rim or counter surface no higher than ____ above the finished floor.
- 32 inches
 - 34 inches
 - 36 inches
 - 38 inches
33. A clear floor space ____ by 48 inches complying with 4.2.4 shall be provided in front of a lavatory to allow forward approach.
- 30 inches
 - 32 inches
 - 34 inches
 - 36 inches
34. If provided, audible emergency alarms shall produce a sound that exceeds the prevailing equivalent sound level in the room or space by at least 15 decibels or exceeds any maximum sound level with a duration of 30 seconds by 5 decibels, whichever is louder. Sound levels for alarm signals shall not exceed ____ decibels.
- 80 decibels
 - 100 decibels
 - 120 decibels
 - 140 decibels

35. Visual alarm devices that are mounted adjacent to emergency exit signs may be used in lieu of flashing exit signs.
- a. true
 - b. false
 - c. not enough information for a specific answer
 - d. too many variable for a specific answer
36. The tops of tables and work surfaces shall be from _____ from the floor or ground.
- a. 24 to 30 inches
 - b. 26 to 32 inches
 - c. 28 to 34 inches
 - d. 30 to 36 inches



Answer Sheet for ADA - Accessibility Standards
 TPDH-00009

****For Office Use only****		
State Board	Course No.	Credit

Please return this answer sheet and your check or money order for \$80.00 to Triton-PDH.com

Please completely fill in one box for each answer

	A	B	C	D
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				

	A	B	C	D
21				
22				
23				
24				
25				
26				
27				
28				
29				
30				
31				
32				
33				
34				
35				
36				

I hereby certify that I have studied the course materials, and the above answers are my own.
 No other person has helped me complete this examination.

 Signature

 Date

 Print Name

 State + Speciality + Registration No.

TRITON-PDH.COM
6757 W. Charleston Boulevard, Suite B
Las Vegas, NV 89146



INFORMATION SHEET

NAME _____

COMPANY _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

PHONE _____ FAX _____

EMAIL _____

State + Speciality + Registration number _____
(I.E. Nevada CE 12345)

Please return this page with your answer sheet and check or money order for \$80.00 per course.

Please make your check or money order payable to Triton-PDH..

Your test will be graded and a certificate of completion will be mailed back to you upon passing your exam.

If you do not pass your exam, the incorrect questions will be highlighted and returned for your use while taking the exam again. All re-exams shall be billed at the original cost of \$80.00.